

**PS and PSG Series
General Purpose Batteries**

Model	Nominal Voltage V	Nominal Capacity A.H.	Current @ 20-hr Rate mA	Length mm.	Width mm	Height mm	Ht. Over Terminal mm	Weight kgs	Terminal Type Standard	Spec Sheet
PS-260	2	6.0	300	50	34	100	105	0.40	F1	
PS-445	4	4.5	225	48	53	94	98	0.59	F2	
PSG-450	4	5.0	250	90	49	73	73	0.40	F2	
PSG-480	4	8.0	400	90	49	102	102	0.95	F2	
PS-490	4	9.0	450	102	44	95	102	1.00	F2	
PS-4100	4	10.0	500	102	50	94	98	1.13	F1	
PS-605	6	0.5	25	57	14	50	50	0.09	WL	
PS-610	6	1.1	55	51	42	51	56	0.20	F1	
PS-612	6	1.4	70	97	24	51	56	0.30	F1	
PSG-625	6	2.5	125	105	41	69	69	0.53	F1	
PS-628	6	2.9	145	66	33	98	103	0.59	F1	
PS-630	6	3.5	175	134	34	60	65	0.62	F1	
PS-632	6	3.5	175	66	33	118	122	0.62	F1	
PS-640	6	4.4	225	70	47	100	108	0.73	F1	
PS-650LS & LF	6	5.0	250	67	67	100	118	0.82	F1 or SP	
PSG-650	6	5.0	250	134	49	76	76	0.98	F2	
PS-665	6	6.5	325	98	56	96	102	1.22	FP	
PS-670	6	7.0	350	151	34	94	100	1.10	F1	
PSG-680	6	8.0	400	134	49	101	101	1.45	F2	
PS-682	6	9.0	450	98	56	118	120	1.45	F1	
PS-6100	6	12.0	600	151	51	94	98	1.95	F1 or F2	
PS-6120FP	6	13.0	650	108	71	141	141	2.18	FP	
PS-6120 Toy	6	13.0	650	108	71	141	141	2.18	TH or TS	
PS-6200	6	20.0	1000	157	83	125	125	3.22	NB1	
PS-6360	6	36.0	1800	159	85	165	176	5.49	F2 or NB1	
PS-6580	6	58.0	2900	185	112	205	205	8.85	F2	
PS-62000	6	210.0	10500	306	169	220	228	29.00	T8	
PS-832	8	3.2	160	134	36	63	69	0.75	F1	
PS-1208	12	0.8	40	96	25	62	n/a	0.35	WL	

**PS and PSG Series
General Purpose Batteries**

Model	Nominal Voltage V	Nominal Capacity A.H.	Current @ 20-hr Rate mA	Length mm.	Width mm	Height mm	Ht. Over Terminal mm	Weight kgs	Terminal Type Standard	Spec Sheet
PS-1212	12	1.4	70	96	43	52	58	0.54	F1	
PS-1220	12	2.5	125	178	35	60	65	0.95	F1	
PS-1221	12	2.0	100	143	24	65	65	0.59	PC	
PS-1221S	12	2.0	100	150	20	89	n/a	0.68	F1/0	
PS-1223	12	2.3	115	182	24	61	61	0.77	PC	
PS-1227	12	2.9	145	79	56	99	105	1.09	F1	
PS-1228	12	2.8	140	133	33	97	104	1.18	F1	
PS-1229	12	2.9	145	178	35	60	66	1.04	F1	
PS-1230	12	3.4	170	133	67	60	66	1.32	F1	
PS-1238	12	3.8	190	195	47	74	76	1.59	F1	
PS-1250	12	5.0	250	90	70	101	107	1.59	F1 or F2	
PS-1251FP	12	5.4	270	140	48	102	103	1.86	FP	
PS-1270	12	7.0	350	151	65	94	98	2.18	F1 or F2	
PS-1272	12	7.2	360	151	65	94	98	2.63	F1 or F2	
PS-1282L	12	9.0	450	196	56	118	118	3.13	F1	
PS-1282S	12	9.0	450	98	112	118	118	3.13	F1	
PS-1290	12	9.0	450	151	65	94	98	2.72	F2	
PS-12100	12	12.0	600	151	102	94	98	3.69	F1 or F2	
PS-12120	12	12.0	600	151	98	94	100	3.59	F2	
PS-12120L	12	12.0	600	215	70	146	146	3.99	FP	
PS-12140	12	14.0	700	151	98	94	100	4.20	F2	
PS-12180	12	18.0	900	181	76	167	167	5.72	F2 or NB2	
PS-12260	12	26.0	1300	167	177	125	125	7.71	F2 or NB2	
PS-12280	12	28.0	1400	165	125	177	177	9.39	NB1	
PS-12330	12	33.0	1650	196	131	158	178	10.50	NB3	
PS-12350	12	35.0	1750	196	131	158	178	11.20	NB3	
PS-12400	12	40.0	2000	197	165	170	170	29.10	NB4	
PS-12550	12	55.0	2750	230	138	207	228	36.00	U	
PS-12750	12	75.0	3750	260	168	207	228	50.60	U	

**PS and PSG Series
General Purpose Batteries**

Model	Nominal Voltage V	Nominal Capacity A.H.	Current @ 20-hr Rate mA	Length mm.	Width mm	Height mm	Ht. Over Terminal mm	Weight kgs	Terminal Type Standard	Spec Sheet
PS-121000	12	100.0	5000	305	168	207	228	68.00	U	
PS-121100	12	110.0	5500	330	171	212	220	69.50	T11	
PS-1400FR	12	140.0	7000	343	171	274	283	99.00	T11	

PS & PSG General Purpose Batteries

All PS and PSG Series Batteries feature:

Absorbent Glass Mat (AGM) technology for superior performance.

Valve regulated, spill proof construction allows safe operation in any position.

Power/volume ratio yielding unrivaled energy density.

Approved for transport by air. D.O.T., I.A.T.A. and F.A.A. certified.

U.L. recognized under file number MH 20845.

CE certified.