

**PSH Series High-Rate Discharge Batteries**

<b>Model</b>	<b>Nominal Voltage V</b>	<b>Nominal Capacity A.H.</b>	<b>Current @ 20-hr Rate mA</b>	<b>Length mm</b>	<b>Width mm</b>	<b>Height mm</b>	<b>Ht. Over Terminal mm</b>	<b>Weight kgs</b>	<b>Terminal Type Standard</b>	<b>Spec Sheet</b>
PSH-655 FR	6	5.5	275	70	47	100	106	0.95	F1	
PSH-1255FR	12	6.0	300	90	70	101	107	1.81	F2	
PSH-1280FR	12	8.5	425	151	65	94	98	2.72	F2	
PSH-12100FR	12	10.5	525	151	65	111	117	3.18	F2	
PSH-1280FR	12	21.0	1050	161	77	167	167	5.99	NB2	

All PSH series batteries are designed specifically for high-rate discharge (UPS) applications. They feature:  
 Absorbent Glass Mat (AGM) technology for superior performance.  
 Rugged plastic case and cover, flame retardant to UL94 V-O.  
 Approved for transport by air. D.O.T., I.A.T.A. and F.A.A. certified.  
 U.L. recognized under file number MH 20845.  
 CE certified.