

Model	Nominal Voltage V	Rated Capacity AH		CCA	Length	Width	Height	Ht. Over Terminal	Weight	Terminal Type Standard	Cross to
		20-hr	10-hr		mm.	mm.	mm.	mm	kgs.		
PDC-1285	12	8.6	8.0	90	151	65	94.5	100	2.75	F2	LPC12-8.0
PDC-12140	12	13.9	13.0	150	151	98	95	101	4.2	F2	LPC12-13
PDC-12200	12	21.0	20.0	290	181.5	98	167.5	167.5	6.6	NB	LPC12-20
PDC-12260	12	27.8	26.0	190	166.5	175	125	125	9.8	NB	LPC12-26
PDC-12350	12	35.4	33.0	225	195	130	164	180	11.2	NB	LPC12-33
PDC-12400	12	40.7	38.0	385	197	165	170	170	14.5	B (T6)	LPC12-38
PDC-12600	12	59.0	55.0	535	228	137	210	230	17.7	U (T9)	LPC12-55
PDC-12800	12	80.4	75.0	585	260	168	208	214	21.0	U (T14)	LPC12-75
PDC-121000	12	100	92.0	710	306	168	210	229	65.3	U (T14)	LPC12-90H
PDC-121100	12	107.2	100.0	790	330	173	212	220	30.0	B (T6)	LPC12-100
PDC-122000	12	214.4	200.0	1250	522	240	218	224	62.5	B (T11)	LPC12-200