

POWERSTEADY

SERIES (AU)

400-3000 VA

LINE INTERACTIVE UPS

FEATURES

- Compact space saving design
- LCD Display
- Line-interactive technology
- Automatic Voltage Regulation (AVR) with boost and buck function
- Microprocessor control
- Auto charging in off mode
- Auto-restart
- Cold Start Function
- Intelligent battery management
- Smart RS232/USB communication Interfaces
- RJ11/RJ45 protection
- AS/NZS 3112 sockets



REAR VIEW



POWERSTEADY SERIES (AU)

400-3000 VA LINE INTERACTIVE UPS

MODEL	POWERSTEADY 400	POWERSTEADY 600	POWERSTEADY 800	POWERSTEADY 1000	POWERSTEADY 1200	POWERSTEADY 1500	POWERSTEADY 2000	POWERSTEADY 2400	POWERSTEADY 3000
Capacity	400VA	600VA	800VA	1000VA	1200VA	1500VA	2000VA	2400VA	3000VA
INPUT									
Voltage	110/120 VAC or 220/240/240 VAC								
Voltage Range	81-145 VAC/ 162-290 VAC								
Frequency Range	60/50 Hz (auto sensing)								
OUTPUT									
AC Voltage Regulation (Batt.Mode)	±10%								
Frequency Range (Batt.Mode)	60 Hz or 50 Hz ± 1 Hz								
Transfer Time	Typical 2-6 ms, 10 ms max.							Typical 10 ms, 13 ms max.	
Waveform (Batt.Mode)	Simulated Sine Wave								
BATTERY									
Battery Type & Number	12V/4.5AH x 1	12V/7AH x 1	12V/9AH x 1	12V/7AH x 2	12V/7AH x 2	12V/9AH x 2	12V/9AH x 2	12V/7AH x 4	12V/9AH x 4
Typical Recharge Time	6-8 hours recover to 90% capacity								
INDICATION									
Display	LCD								
PROTECTION									
Full Protection	Overload and overcharge								
ALARM									
Battery Mode	Sounding every 10 seconds								
Low Battery	Sounding every second								
Overload	Sounding every 0.5								
Battery Replacement Alarm	Sounding every 2 seconds								
Fault	Continuously Sounding								
PHYSICAL									
Dimension WxDxH (mm)	101 x 142 x 298			149.3 x 162 x 338		158 x 198 x 380		213 x 145 x 436	
Net Weight (kg) ³	.554	.254	.7	7.88		10.1	10.5	19.82	3
OPERATING ENVIRONMENT									
Humidity	0-90% RH @ 0-40°C (non-condensing)								
Noise Level	Less than 40dB								
MANAGEMENT									
Optional USB/	Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC								